



# TRIPLE X 6000 lb (2720 kg)



**Ramsey Triple X 6000 lb (2720kg) single line pull**  
**Powerful 5.5 hp motor with 90:1 planetary reduction provides high speed and high performance, combined with the reliability of a quality Ramsey USA built winch**

### Features

**Solenoid control with remote, Power forward and reverse, Technora synthetic rope, Automatic brake & Free spool**

### Specifications

Rated Line Pull	1st Layer 6000 lb ( 2720 kg)
Gear Ratio	90:1 planetary reduction
Motor	5.5 hp (4 kW) 12 volt DC
Drum	Steel 63 mm diameter x 99 mm wide
Rope (High Temp)	Technora synthetic 9mm x 10.7 M
Mounting Pattern	139.9 mm x 114.3 mm (4 Bolt)
Dimensions	434 mm x 155.7 mm x 203.4 mm
Weight	Boxed 28.5 kg

### Performance 1st layer

<b>PULL</b>	lbs	0	1000	3000	5000	6000
	kgs	0	450	1350	2260	2720
<b>SPEED</b>	fpm	45	23	20	14	12
	mpm	13.7	7	6.1	4.3	3.7
<b>CURRENT</b>	Amps 12 v	100	200	270	350	405

	<u>1st Layer</u>	<u>2nd layer</u>	<u>3rd Layer</u>	<u>4th Layer</u>
<b>Line Pull</b>	6000lb (2722kg)	4700lb (2130kg)	3900lb (1760kg)	3300lb (1490kg)
<b>Rope capacity</b>	5 ft (1.5m)	15 ft (4.6m)	25 ft (7.6m)	35 ft (10.5m)