



# BC450 Aug

## Grain Auger Winch

- 1ST LAYER 3500 lbs. (15.4KN)
- SAFETY FACTOR LIFTING at 5:1 (453 kg)
- MECHANICAL & DYNAMIC BRAKING
- PLANETARY **LARGER GEARING** 3 Stage
- 1.6 HP (1.2 kW) 12 volt MOTOR
- SUITABLE FOR STEEL OR SYNTHETIC ROPE
- MOUNTABLE SWITCH + SHUT OFF SWITCH
- SEALED WEATHER PROOF



<u>Line Pull in kg (lb's)</u>	<u>Line Speed M p/m (Ft p/m)</u>	<u>Current Draw Amps 12V</u>
0 load	7.5 (24.6)	23 Amps
227 kg (500 lb)	5.9 (19.3)	45 Amps
454 kg (1000 lb)	5.0 (16.4)	73 Amps
680 kg (1500 lb)	4.5 (14.8)	98 Amps
907 kg (2000 lb)	3.9 (12.8)	125 Amps
1134 kg (2500 lb)	3.5 (11.5)	154 Amps
1361 kg (3000 lb)	3.0 (9.8)	183 Amps
1588 kg (3500 lb)	2.6 (8.5)	220 Amps

