

SUPERWINCH

HUSKY10 10000 lb (4545kg)

In 12 or 24 volt DC



The Superwinch Husky10 is designed and engineered for strength and reliability in industrial applications.

SAE J706

Specifications & Standard Features

POWER IN AND POWER OUT
 FREESPOOLING LEVER APPLIED
 BATTERY CABLES WITH TERMINALS
 HEAVY DUTY SEALED 4.2hp (3.15Kw) SERIES WOUND MOTOR
 HEAVY DUTY OIL BATHED WORM BOX WITH SPUR REDUCTION
 FIXED OR RELOCATABLE SOLENOID BOX
 SUBMIRSALE SOLID STATE SOLENOID WITH 4.6M REMOTE
 HIGH TENSILE WIRE ROPE 3/8"x 90' (9.5mm x 27.4 M)

RATED LINE PULL	10000 lb (4536 KG)
GEAR RATIO	294:1
DRUM DIAMETER	3" (76mm)
DRUM LENGTH	9" (229mm)
DIMENSIONS	627mm L x 248mm D x 226mm H
WEIGHT	51 kg

Performance 12v DC on first layer

<u>Line Pull</u> <u>lbs</u>	<u>Line Pull</u> <u>kg</u>	<u>Line Speed</u> <u>FPM</u>	<u>Line Speed</u> <u>M/min</u>	<u>Current 12V</u> <u>Amps</u>
0		22.6	6.9	62
4000	1814	6.3	1.9	205
6000	2722	4	1.2	276
8000	3629	2.5	.8	340
10000	4536	1.5	0.5	450