

Tiger Shark 9,500 SR (Synthetic)

Superwinch **TIGER SHARK SR**
amazing performance



Rated Line Pull	9,500 lbs (4309 kg)
Motor	Sealed 5.2 HP Series Wound
Gearing	3-Stage Planetary
Gear Ratio	218.:1
Solenoid	Weather Sealed Solenoid and Circuit Breaker Protected
Clutch	Pull and Turn, Ergo
Brake	Mechanical, Automatic Load Holding
Rope	Synthetic 3/8" x 80'
Hook	Heavy Duty Clevis Pinned Latched
Fairlead	Anodized Aluminum Hawse
Remote	12' Rubber Sealed Hand-held
Dimensions	20.8" L x 6.3" W x 9.2 H (529mm L x 160mm W x 234.5mm H)
Drum Diameter	2.5" (63.5mm)
Drum Length	9" (228.6mm)
Installed Weight	90 lbs. (41kg) 59 lbs. (26.7kg)
Shipping Weight	94 lbs (42kg) 63 lbs (28.6 kg)
Warranty	Limited 2 Year Warranty
UPC	0 22705 00360 5 0 22705 00365 0
Line Pull: 0 lbs (0 kgs)	80 Amps Motor Draw/19 FPM (5.7 MPM) Line Speed
Line Pull: 9,500 lbs (4,309 kgs)	340 Amps Motor Draw/4 FPM (1.2 M/M) Line Speed
Lead Wires	6' (1.8m) x 4 gauge (25mm ²)

